

- 1. STREET NAME SIGN SHALL BE IN CONFORMANCE WITH THE LATEST EDITION OF THE M.U.T.C.D.
- 2. ALL SIGN LETTERING SHALL BE IN UPPERCASE AND LOWERCASE LETTERS AND LETTERING FONT SERIES B 2000 AS PROVIDED IN THE STANDARD ALPHABETS FOR HIGHWAY SIGNS AND PAVEMENT MARKINGS.
- $\sqrt{3}$. EACH STREET NAME SIGN INSTALLATION SHALL HAVE (4) FLAT PLATE ALUMINUM NO. 6061–T6, .080 GAUGE.
- 4. GREEN SHEETING TRANSPARENCY ElectroCUT FILM 1177C "3M" OR APPROVED EQUAL. GREEN SHEETING TRANSPARENCY FILM SHALL BE FROM THE SAME MANUFACTURER AS WHITE SHEETING
- S. WHITE SHEETING LETTERING SHALL BE RETROREFLECTIVE ASTM IX DIAMOND GRADE VIP "3M" OR APPROVED EQUAL. WHITE SHEETING SHALL BE FROM THE SAME MANUFACTURER AS GREEN TRANSPARENCY FILM.
- 6. EACH STREET NAME SIGN INSTALLATION SHALL INCLUDE (2) SIGNS BACK TO BACK EACH DIRECTION FOR A TOTAL OF (4) STREET NAME SIGNS. SEE DETAIL R-415 FOR TRAFFIC SIGN INSTALLATION.
- CONTACT THE CITY OF RENO'S CORPORATION YARD AT 334-2246 FOR INFORMATION ON THE CITY OF RENO LOGO. LOGO EXTENTS SHALL NOT EXCEED 6 INCHES.
- SIGN LENGTH VARIES 30" MINIMUM TO 42" MAXIMUM. LONGER STREET NAMES AND/OR THE USE OF DROP LETTERS (EXAMPLE LOWERCASE "g" AND "y") REQUIRE APPROVAL FROM CITY TRAFFIC ENGINEER.

